SR RANGE



Outfront mower





SR RANGE DDD OUTFRONT MOWER





Transmission and drive

SR machines are fitted with hydrostatic transmission. In slippy conditions, on uneven ground or on slopes the differential can be locked to further improve traction.

All machines are available as a 4-wheel version with rear floating axle, which provides stability and safety when the operator crosses slopes.

All 4 WD models adopt the patented HTC™ (Hydrostatic Traction Control) system which provides significant advantages: - It intelligently varies the traction supplied to each rear wheels

to prevent them from damaging the turf during turning operations:

- It ensures that traction is still supplied all four wheels, even during turning operations.

Loading tray

SR machines are fitted with a useful, robust loading tray which can be used to transport tools or materials such as sand and soil etc...

These which can then be dumped onto the ground using the hydraulic dump facility. An anti-shock external frame made of heavy-gauge tubular steel protects the loading tray from the impacts that frequently occur when working in confined spaces.







SR machines are multi-purpose front lawnmower. The SR product family includes four versions of hydrostatic machines with petrol or diesel engines and 2 or 4 wheel drive. With SR lawnmowers several attachments can be fitted to ensure an increased return on investment for landscapers and other professionals.





Attachments

All cutting decks are mounted on the front of the machine. This prevents compaction of the grass, improving cut quality and providing improved visibility for the operator. This solution also allows cutting under bushes and makes work around trees and trimming along walls and flowerbeds easier.

Rear Discharge Cutting Deck 130 SP with Mulching Kit

The 130cm rear discharge deck is highly productive. The front profile of the mower deck is raised and fitted with large swinging entry gates to aid the grass entry, which is cut without being compressed. Additionally, a specially designed deflector, allows the deck to be converted from rear discharge to mulching without the need for tools. The deck is also equipped with the innovative "SA" system which allows for the quick adjustment of cutting height via a simple single lever adjustment.

Side discharge cutting deck 130 SL

For operators who prefer the more traditional side discharge, each SR machine can be fitted with the 130cm side discharge deck. The deck is supported by a set of large caster wheels that allows it to float and adapt to the contours of the ground. The deck employs a two-blade-disc cutting system with double articulated blades. Blades are rotated by two cast iron direct drive reduction gearboxes.

Cutting deck 150 SM

A new deck with belt-driven transmission and three blades. In standard form it is configured as a mulching deck. However, it can be converted to side discharge using a special kit supplied jointly. It also incorporates the "SA" system for the quick adjustment of cutting height.

Aerator

The 100 cm aerator is particularly useful in spring or at the end of the summer to remove moss and weeds and to help the grass breathe.



Flail Mower

A rugged flail mower attachment is available for clearing long grass, scrub and even brushwood.



> Front grader blade

The ideal tool to level sand and soil, fill dips in the ground or clear snow.



Snow Thrower

The dedicated 130 cm, doublestage snow thrower comes fitted with hydraulic orientation, allowing the operator control the angle of attack. It is also fitted with a Plexiglas screen to provide additional protection for the operator.

